

Please refer to the attachment for text in other languages
 Bitte entnehmen Sie dem Beilagezettel den Text der anderen Sprachen
 Merci de se référer à l'annexe joint pour le texte dans d'autres langues
 Fare riferimento all'allegato per il testo nelle altre lingue.
 Véase el anexo para el texto en otros idiomas

For at se teksten på andre sprog henvises der til vedlagte produktinformation
 För text på övriga språk hänvisas till bilagan
 Por favor consulte o anexo para informação noutras línguas
 Δείτε στην επισύναψη, το κείμενο σε άλλες γλώσσες.

CE EIGHTCHECK-3WP Assay Sheet

Normal Level

LOT	5290 0822
	23-Jan-2016
Temperature during Assay	25 °C

Model		WBC	RBC	HGB		HCT	MCV	MCH		MCHC		PLT
		10e3/μl	10e6/μl	g/dl	mmol/l	%	fL	pg	fmol	g/dl	mmol/l	10e3/μl
K-800 K-1000 K-4500 1)	Range	8.1	4.57	13.3	8.2	36.6	81.3	30.7	1903	39.8	24.7	260
	Mean	6.9	4.27	12.5	7.8	31.8	73.5	27.7	1721	35.6	22.1	192
	Limit %	7.5	4.42	12.9	8.0	34.2	77.4	29.2	1812	37.7	23.4	226
	Limit #	8.0	3.5	3.0	3.0	7.0	5.0	5.0	5.0	5.5	5.5	15
K-4500 Closed Mode 2)	Range	8.0	4.64	13.4	8.3	36.8	81.3	31.0	1921	40.5	25.2	252
	Mean	6.2	4.20	12.4	7.7	31.6	73.5	27.4	1703	34.9	21.6	186
	Limit %	7.1	4.42	12.9	8.0	34.2	77.4	29.2	1812	37.7	23.4	219
	Limit #	13.0	5.0	4.0	4.0	7.5	5.0	6.0	6.0	7.5	7.5	15
KX-21N KX-21 2)	Range	7.8	4.64	13.3	8.2	37.1	81.3	30.5	1893	40.0	24.8	267
	Mean	6.8	4.28	12.5	7.8	31.9	73.5	27.3	1695	34.8	21.6	197
	Limit %	7.3	4.46	12.9	8.0	34.5	77.4	28.9	1794	37.4	23.2	232
	Limit #	7.0	4.0	3.0	3.0	7.5	5.0	5.5	5.5	7.0	7.0	15
F-800 F-820	Range	8.2	4.68	13.8	8.5	40.1	90.0	31.5	1.95	37.7	23.3	259
	Mean	6.8	4.24	12.4	7.7	34.9	78.2	27.3	1.69	32.1	19.9	191
	Limit %	7.5	4.46	13.1	8.1	37.5	84.1	29.4	1.82	34.9	21.6	225
	Limit #	9.0	5.0	5.0	5.0	7.0	7.0	7.0	8.0	8.0	8.0	15
F-300 F-500 F-520	Range	8.2	4.68	13.8	8.5	40.1	89.9	31.5	1.95	37.7	23.3	243
	Mean	6.8	4.24	12.4	7.7	34.9	78.1	27.3	1.69	32.1	19.9	169
	Limit %	7.5	4.46	13.1	8.1	37.5	84.0	29.4	1.82	34.9	21.6	206
	Limit #	9.0	5.0	5.0	5.0	7.0	7.0	7.0	8.0	8.0	8.0	18
pochI-100i 2)	Range	8.0	4.86	13.4	8.3	40.6	86.1	29.3	1816	36.4	22.6	255
	Mean	6.6	4.40	12.2	7.5	34.6	76.3	25.9	1610	31.6	19.6	189
	Limit %	7.3	4.63	12.9	7.9	37.6	81.2	27.6	1713	34.0	21.1	222
	Limit #	9.0	5.0	5.0	5.0	8.0	6.0	6.0	6.0	7.0	7.0	15
XP-Series 2)	Range	7.5	4.58	12.9	8.0	36.6	81.2	30.1	1866	39.5	24.5	273
	Mean	6.5	4.22	12.1	7.6	31.4	73.4	26.9	1672	34.3	21.3	201
	Limit %	7.0	4.40	12.5	7.8	34.0	77.3	28.5	1769	36.9	22.9	237
	Limit #	7.0	4.0	3.0	3.0	7.5	5.0	5.5	5.5	7.0	7.0	15

Model		W-SCR	W-MCR	W-LCR	W-SCC	W-MCC	W-LCC	W-SMV	W-LMV	RDW-CV	RDW-SD	PDW	MPV	P-LCR	PCT
		%	%	% 3)	10e3/μl 3)	10e3/μl 3)	10e3/μl 3)	fL	fL	%	fL	fL	fL	%	%
K-1000 K-4500 1)	Range	32.6	12.3	62.9	2.5	0.9	4.8	66.4	202.1	13.6	30.4	8.0	10.3	21.5	
	Mean	28.4	9.1	54.7	2.1	0.7	4.0	46.2	172.1	10.0	22.4	6.6	8.7	7.1	
	Limit %	30.5	10.7	58.3	2.3	0.8	4.4	56.3	187.1	11.8	26.4	7.3	9.5	14.3	
	Limit #	7.0	15.0	7.0	10.0	15.0	10.0	18.0	8.0	15.0	15.0	10.0	8.0	50.0	
K-4500 Closed Mode 2)	Range	32.6	12.3	62.9	2.4	0.9	4.5	66.4	202.1	13.6	30.4	8.0	10.3	21.5	
	Mean	28.4	9.1	54.7	2.0	0.7	3.7	46.2	172.1	10.0	22.4	6.6	8.7	7.1	
	Limit %	30.5	10.7	58.3	2.2	0.8	4.1	56.3	187.1	11.8	26.4	7.3	9.5	14.3	
	Limit #	7.0	15.0	7.0	10.0	15.0	10.0	18.0	8.0	15.0	15.0	10.0	8.0	50.0	
KX-21N KX-21	Range	35.2	13.3	62.9	2.5	1.0	4.7	74.6	223.8	11.7	38.0	8.7	10.0	18.9	
	Mean	26.0	7.9	54.7	1.9	0.6	3.9	51.8	165.4	8.7	28.0	7.1	8.6	6.3	
	Limit %	30.6	10.6	58.8	2.2	0.8	4.3	63.2	194.6	10.2	33.0	7.9	9.3	12.6	
	Limit #	15.0	25.0	7.0	15.0	25.0	10.0	18.0	15.0	15.0	10.0	10.0	8.0	50.0	
F-800 F-820	Range	37.1		77.9	2.7		5.5			18.3	48.5	8.9	11.6		
	Mean	27.5		57.5	2.0		4.3			12.1	35.9	5.3	7.8		
	Limit %	32.3		67.7	2.4		5.1			14.2	42.2	7.1	9.7		
	Limit #	15.0		15.0	15.0		15.0			15.0	15.0	25.0	20.0		
pochI-100i	Range	35.4	12.4	63.7	2.5	0.9	4.9	77.6	223.8	18.6	50.5	8.8	11.1	22.6	
	Mean	26.2	7.0	55.3	1.9	0.5	3.9	54.0	165.4	13.8	37.3	7.2	9.5	5.6	
	Limit %	30.8	9.7	59.5	2.2	0.7	4.4	65.8	194.6	16.2	43.9	8.0	10.3	14.1	
	Limit #	15.0	28.0	7.0	15.0	28.0	12.0	18.0	15.0	15.0	10.0	10.0	8.0	60.0	
XP-Series	Range	35.5	12.9	62.9	2.5	0.9	4.5	75.9	224.1	11.4	38.5	8.6	10.2	19.4	0.32
	Mean	26.3	7.7	54.7	1.9	0.5	3.7	52.7	165.7	8.4	28.5	7.0	8.6	6.4	0.12
	Limit %	30.9	10.3	58.8	2.2	0.7	4.1	64.3	194.9	9.9	33.5	7.8	9.4	12.9	0.22
	Limit #	15.0	25.0	7.0	15.0	25.0	10.0	18.0	15.0	15.0	15.0	10.0	8.0	50.0	43.0

Remarks:

- 1) K-4500: Open Mode assay values
- 2) MCH value in amol and not in fmol

3) These parameters values should be used as a reference only

Please refer to the attachment for text in other languages
 Bitte entnehmen Sie dem Beilagezettel den Text der anderen Sprachen
 Merci de se référer à l'annexe joint pour le texte dans d'autres langues
 Fare riferimento all'allegato per il testo nelle altre lingue.
 Véase el anexo para el texto en otros idiomas

For at se teksten på andre sprog henvises der til vedlagte produktinformation
 För text på övriga språk hänvisas till bilagan
 Por favor consulte o anexo para informação noutras línguas
 Δείτε στην επισύναψη, το κείμενο σε άλλες γλώσσες.

CE EIGHTCHECK-3WP Assay Sheet

High Level

LOT

5289 0823

23-Jan-2016

Temperature during Assay

25°C

Model		WBC	RBC	HGB		HCT	MCV	MCH		MCHC		PLT
		10e3/ μ l	10e6/ μ l	g/dl	mmol/l	%	fL	pg	femol	g/dl	mmol/l	10e3/ μ l
K-800	Range	20.2	5.50	17.6	10.9	48.3	89.1	33.8	2098	39.8	24.7	599
K-1000		17.2	5.12	16.6	10.3	41.9	80.7	30.6	1898	36.0	22.3	461
K-4500 1)	Mean	18.7	5.91	17.1	10.6	45.1	84.9	32.2	1998	37.9	23.5	530
2)	Limit %	8.0	3.5	3.1	3.1	7.0	5.0	5.0	5.0	5.0	5.0	13
K-4500	Range	20.1	5.60	17.9	11.1	48.5	89.1	34.1	2118	40.7	25.3	581
Closed Mode		15.5	5.02	16.3	10.1	41.7	80.7	30.3	1878	35.1	21.7	447
2)	Mean	17.9	5.31	17.1	10.6	45.1	84.9	32.2	1998	37.9	23.5	514
	Limit %	13.0	5.5	4.5	4.5	7.5	5.0	6.0	6.0	7.5	7.5	13
KX-21N	Range	19.3	5.54	17.9	11.1	48.8	89.5	34.3	2128	40.8	25.3	637
KX-21		16.7	5.12	16.7	10.3	42.0	80.9	30.7	1906	35.4	21.9	491
2)	Mean	18.0	5.33	17.3	10.7	45.4	85.2	32.5	2017	38.1	23.6	564
	Limit %	7.0	4.0	3.5	3.5	7.5	5.0	5.5	5.5	7.0	7.0	13
	Limit #	1.3	0.21	0.8	0.4	3.4	4.3	1.8	1.1	2.7	1.7	73
F-800	Range	20.8	5.64	18.3	11.3	52.2	97.3	34.7	2.15	38.6	23.9	615
F-820		17.4	5.10	16.5	10.3	45.4	84.5	30.1	1.87	32.8	20.3	455
	Mean	19.1	5.37	17.4	10.8	48.8	90.9	32.4	2.01	35.7	22.1	535
	Limit %	9.0	5.0	5.0	5.0	7.0	7.0	7.0	7.0	8.0	8.0	15
F-300	Range	20.8	5.64	18.3	11.3	52.2	97.4	34.7	2.15	38.6	23.9	551
F-500		17.4	5.10	16.5	10.3	45.4	84.6	30.1	1.87	32.8	20.3	383
F-520	Mean	19.1	5.37	17.4	10.8	48.8	91.0	32.4	2.01	35.7	22.1	467
	Limit %	9.0	5.0	5.0	5.0	7.0	7.0	7.0	7.0	8.0	8.0	15
pocH-100i	Range	19.9	5.81	18.2	11.2	53.5	94.9	33.0	2049	37.3	23.2	613
2)		16.7	5.25	16.4	10.2	45.5	84.1	29.6	1835	32.5	20.2	453
	Mean	18.3	5.53	17.3	10.7	49.5	89.5	31.3	1942	34.9	21.7	533
	Limit %	9.0	5.0	5.0	5.0	8.0	6.0	5.5	5.5	7.0	7.0	15
	Limit #	1.6	0.28	0.9	0.5	4.0	5.4	1.7	1.07	2.4	1.5	80
XP-Series	Range	18.6	5.48	17.4	10.8	48.2	89.4	33.5	2083	40.0	24.8	641
2)		16.2	5.06	16.2	10.0	41.4	80.8	30.1	1865	34.8	21.6	493
	Mean	17.4	5.27	16.8	10.4	44.8	85.1	31.8	1974	37.4	23.2	567
	Limit %	7.0	4.0	3.5	3.5	7.5	5.0	5.5	5.5	7.0	7.0	13
	Limit #	1.2	0.21	0.6	0.4	3.4	4.3	1.7	1.09	2.6	1.6	74

Model		W-SCR	W-MCR	W-LCR	W-SCC	W-MCC	W-LCC	W-SMV	W-LMV	RDW-CV	RDW-SD	PDW	MPV	P-LCR	PCT
		%	%	% 3)	10e3/ μ l 3)	10e3/ μ l 3)	10e3/ μ l 3)	fL	fL	%	fL	fL	fL	%	%
K-1000	Range	35.7	19.0	53.6	6.8	3.6	10.3	60.3	205.0	12.3	33.1	9.2	10.8	30.6	
K-4500 1)		31.1	14.0	46.6	5.6	2.6	8.5	41.9	174.6	9.1	24.5	7.6	9.2	10.2	
	Mean	33.4	16.5	50.1	6.2	3.1	9.4	51.1	189.8	10.7	28.8	8.4	10.0	20.4	
	Limit %	7.0	15.0	7.0	10.0	15.0	10.0	18.0	8.0	15.0	15.0	10.0	8.0	50.0	
K-4500	Range	38.4	20.6	57.6	7.1	3.6	10.8	60.3	220.2	12.6	34.0	10.1	11.0	32.6	
Closed Mode		28.4	12.4	42.6	4.7	2.2	7.2	41.9	159.4	8.8	23.6	6.7	9.0	8.2	
	Mean	33.4	16.5	50.1	5.9	2.9	9.0	51.1	189.8	10.7	28.8	8.4	10.0	20.4	
	Limit %	15.0	25.0	15.0	20.0	25.0	20.0	18.0	16.0	18.0	18.0	20.0	10.0	50.0	
KX-21N	Range	39.6	20.5	52.6	7.1	3.8	9.7	71.7	225.5	10.9	39.4	9.9	10.6	27.9	
KX-21		29.2	12.3	45.8	5.3	2.2	7.9	49.9	166.7	8.1	29.2	8.1	9.0	9.3	
	Mean	34.4	16.4	49.2	6.2	3.0	8.8	60.6	196.1	9.5	34.3	9.0	9.8	18.6	
	Limit %	15.0	25.0	7.0	15.0	25.0	10.0	18.0	15.0	15.0	15.0	10.0	8.0	50.0	
	Limit #	5.2	4.1	3.4	0.9	0.8	0.9	10.9	29.4	1.4	5.1	0.9	0.8	9.3	
F-800	Range	42.2		72.8	7.3		12.5			17.9	52.0	10.5	12.0		
F-820		31.2		53.8	6.0		10.3			13.3	38.4	6.3	8.0		
	Mean	36.7		63.3	7.0		12.1			15.6	45.2	8.4	10.0		
	Limit %	15.0		15.0	15.0		15.0			15.0	15.0	25.0	20.0		
pocH-100i	Range	40.9	19.1	53.0	7.5	3.5	10.2	74.8	223.0	18.2	54.2	10.0	11.4	31.2	
		30.3	10.7	46.0	5.5	1.9	8.0	52.0	164.8	13.4	40.0	8.2	9.8	7.8	
	Mean	35.6	14.9	49.5	6.5	2.7	9.1	63.4	193.9	15.8	47.1	9.1	10.6	19.5	
	Limit %	15.0	28.0	7.0	15.0	28.0	12.0	18.0	15.0	15.0	15.0	10.0	8.0	80.0	
	Limit #	5.3	4.2	3.5	1.0	0.8	1.1	11.4	29.1	2.4	7.1	0.9	0.8	11.7	
XP-Series	Range	39.6	20.5	52.6	6.9	3.5	9.5	72.8	225.9	10.5	39.0	9.7	10.7	28.7	0.80
		29.2	12.3	45.8	5.1	2.1	7.7	50.6	166.9	7.7	28.8	7.9	9.1	9.5	0.32
	Mean	34.4	16.4	49.2	6.0	2.8	8.6	61.7	196.4	9.1	33.9	8.9	9.9	19.1	0.56
	Limit %	15.0	25.0	7.0	15.0	25.0	10.0	18.0	15.0	15.0	15.0	10.0	8.0	50.0	43.0
	Limit #	5.2	4.1	3.4	0.9	0.7	0.9	11.1	29.5	1.4	5.1	0.9	0.8	9.6	0.24

Remarks:

- 1) K-4500: Open Mode assay values
- 2) MCH value in amol and not in fmol

- 3) These parameters values should be used as a reference only